



Product Data Sheet

Product Type : USZ#1 Grease Grade		
Description : Fine metal powder optimally sized by screening.		
Specification :		USZ#1GG
Total Zinc	% min.	98
Metallic Zinc	% min.	94
Lead, Cadmium, Iron	% max.	1.0
Average Particle Size	microns	4 -10
Sieve +100 mesh (150 μ)	% max.	Trace
+200 mesh (75 μ)	% max.	0.1
+325 mesh (44 μ)	% max.	10.0
Specific Gravity		7.1
Typical Applications : Grease Lubricants Chemicals		
Packaging : Standard - up to 100 # in pails, up to 500 # in fiber drums, above 1,000 # in super sacks. Custom packaging upon request.		
Storage & Shelf Life : Zinc dust is sensitive to moisture - store in a cool, dry area. Unsealing containers or storing in a humid area will reduce the shelf life.		
Alternative Grades: Calcium oxide additive is available at request.		
U.S. ZINC Products : Zinc dust ; Zinc fines ; Zinc metal ; Zinc oxide.		
The information contained herein has been compiled to the best of US Zinc's knowledge, but is presented without any obligation. US Zinc assumes no liability for infringement of any patent which may result from the use of this information or products.		

Office : 6020 Navigation Blvd.
Houston, Texas 77011.
Mail: P.O.Box 611,
Houston, Texas 77001.

Tel: (713) 926-1705
Fax: (713) 924-4824
email: dustinfo@uszinc.com
web site: www.uszinc.com

(PDS-USZ#1 GG)

Review date 08/10/09 S. Nanavati